



MASLAND SEAM SEALER

MASLAND SEAM SEALER is a strong adhesive with superior bond and tensile strength when dry. It does not contain ammonia, is non-flammable, and dries to a clear film that is highly water resistant. **MASLAND SEAM SEALER** has low odor and "zero" calculated VOC's, which makes it ideal for use in schools, public buildings, and other areas where odor is a concern.

Features:

- Very quick, strong bond development. Dries clear.
- Low odor. Does not contain ammonia or solvents.
- Water clean up when wet. Water resistant when dry.
- CRI Green Label Plus Approved.
- Passes water penetration test at 10,000 + cycles on prepared carpet seams

Applications:

Carpet - Eliminate seam unraveling on direct-glue and double-glue broadloom carpet installations. Use with Masland Woven Polypropylene and Masland High Performance Backing (Urethane).

Directions for Use:

1. Prepare the floor covering according to Masland's instructions.
2. Apply continuous bead of seam sealer along the edge of the backing on the first piece of carpet or sheet.
3. Immediately place the edge of the second piece of floor covering into contact with the first piece which has the seam sealer on it. To achieve a good bond, it is essential for the two pieces to have a tight fit, and traffic on the seamed area should be restricted for at least 24 hours.
4. Clean any smears of seam sealer or adhesive with water while material is in the wet state. Dried residues may require the use of an adhesive remover.

Coverage: Approximately 400 linear feet per 32 oz. bottle using 1/8" bead

130107