



## **MASLAND PREMIUM CARPET ADHESIVE**

**MASLAND PREMIUM CARPET ADHESIVE** is designed for direct glue down interior carpet installations and for bonding carpet to pad in double-stick systems.

**MASLAND PREMIUM CARPET ADHESIVE** quickly develops adhesive legging and forms a strong durable bond with most commercial broadloom carpets. The adhesive remains tacky for an extended period of time, has little odor and is environmentally friendly.

The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65°- 95° F, and the humidity below 65% for 48 hours prior to, during, and after the testing and installation.

Use **MASLAND PREMIUM CARPET ADHESIVE** on concrete substrates with in-situ Relative Humidity per ASTM F2170 up to 80% RH and with surface pH from 7 - 9. Site conditions and substrate preparations must comply with those specified by the Carpet & Rug Institute (CRI104).

The substrate must be sound, smooth, dry and clean. Remove any dirt, wax, loose paint, existing adhesives, concrete sealers, curing and parting agents, and all other foreign matter that would interfere with a good bond. Do not use on substrates that have been chemically cleaned. Seal porous or dusty concrete surfaces with an approved sealer. Lay flooring into adhesive that is still wet enough to ensure 100% transfer to the flooring backing, and roll with a 75-100 lb. roller. When installing over a non-porous surface, let adhesive become tacky.

Open time: 15-25 minutes

Trowel Size: 1/8" x 1/8" x 1/16" V-Notch: 36-40 square yards per pail

### **CLEAN UP:**

Use a clean wet cloth to clean up adhesive while still wet; dried adhesive may require the use of an appropriate solvent cleaner.

### **Shelf Life:**

1 year from manufacturing date in an unopened container

VOC Content: Compliant with California SCAQMD Rule 1168

130107