

PRODUCT SPECIFICATIONS

Style	8319
Construction	High Performance Luxury Vinyl Tile (SPC)
Layers	0.165" (4.2mm) Extruded Solid Polymer Core (SPC) 0.039" (1.0mm) Pre-Attached HDPE Underlayment
Wear Layer	20 mil (0.5mm)
Edge Detail	Micro-beveled Edge
Finish	Urethane with Ceramic Bead
Embossing	Natural Timber
Overall Thickness	0.205" (5.2mm)
Installation Type	Click

PACKAGING

Tile Size	7.08" x 47.64" (18cm x 121cm)	Coverage/Piece	2.342 Sq. Ft. (0.2176 m ²)
Pieces per box	10	Coverage/Carton	23.42 Sq. Ft. (2.176 m ²)
Square feet per box	23.42 (2.175 m ²)	Coverage/Pallet	52 Cartons (1217 Sq. Ft. / 113.1 m ²)
		Coverage/Container	20 Pallets (24,356 Sq. Ft. / 2,263 m ²)

TESTING

TEST	STANDARD	MINIMUM REQUIREMENT	RESULTS
Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm ² (Class 1)	Passes
Smoke Density	ASTM E662	≤450	Passes
Slip Resistance	ASTM D2047	N/A	≥0.6 (Dry)
Heavy Metals	ASTM F963	Refer to Standard	Passes
Static Load	ASTM F970	≤0.005", 250 lbs. load	Passes
Static Load Limit	SIM Test	Test to Limit (±0.005")	≥1000 lbs.
Chemical Resistance	ASTM F925	No more than slight change	Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max	Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max	Passes
Abrasion Resistance	ASTM D4060	N/A	≥20,000 Cycles
Impact Sound Transmission**	ASTM E492	Impact Insulation Class (IIC) ≥50	IIC 67
Airborne Sound Transmission Loss**	ASTM E90	Sound Transmission Class (STC) ≥50	STC 61
Indoor Air Quality	CHPS 01350 LEED EQ 4.3	Low VOC	FloorScore Certified

WARRANTY

Commercial 15 Year - Limited Commercial Wear Warranty

See warranty documentation for full details of terms and conditions.

**Tested over 6" concrete slab with drop-ceiling.

